Data sheet STLW1000

STLW1000

Suretime Outdoor PIR White

Features & Benefits

- Manual override (Pulse) for extended light on times.
- Adjustable time ON setting.
- Adjustable lux level.
- Knockouts to allow cable entry from underneath the PIR.



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface
Earth Class Rating	Class II
Operating Temperature	-20°C to 40°C
Ingress Protection Rating	IP55
Setting Type	Dial
Approved Mounting Height (m)	2.5
Motion Detection (m)	8 to 12
Detection Angle	180°
Mounting Hole Centres (mm)	58
Standby Consumption	<1W
Number of Channels	1



Subject to technical changes and revisions

additional information at: https://www.timeguard.com This data was generated on

Data sheet STLW1000

Switch rating	200W LED, 1000W Halogen, 200W
	Fluorescent/Low Energy Lighting
ON Time Adjustment	3 Seconds to 18 Minutes. User Adjustable
Lux Level	10 to 1000
Detection Range (M)	8 to 12
Permanent ON Facility	Yes (Pulse Override)
Dusk Till Dawn	No
Multiple Unit Support	Up to 5 Units In Parallel
Cable Entry(s)	Back Entry, Bottom Entry

General

Weight (g)	119
Height (mm)	76
Width (mm)	76
Depth (mm)	87
Body Construction	Polycarbonate
Product Colour	White
Accessories (Included)	Fittings (Rawl Plugs, Screws)
EAN Number	5012483014318
Guarantee Period	2 Years
Trade Tariff Commodity Code	8536508090




Subject to technical changes and revisions

additional information at: https://www.timeguard.com This data was generated on

Data sheet STLW1000

Light / PIR Presence Detectors

Line Diagrams





Subject to technical changes and revisions

additional information at: https://www.timeguard.com

This data was generated on

09/10/2023